



**Vendor:** Cisco

**Exam Code:** 642-737

**Exam Name:** Implementing Advanced Cisco Unified  
Wireless Security (IAUWS) v2.0

**Version:** DEMO

### QUESTION 1

What device will authenticate the user when a sponsor creates a guest account on the Cisco NGS?

- A. WLAN controller
- B. Cisco ACS
- C. Cisco NGS
- D. active directory server

**Answer: C**

### QUESTION 2

A lobby ambassador is creating guest access accounts. At which two locations can the accounts be stored? (Choose two.)

- A. NAC guest server
- B. Active directory
- C. WLAN controller
- D. WCS
- E. ACS

**Answer: CD**

### QUESTION 3

An engineer is configuring the guest WLAN to redirect to a created login page uploaded to the controller. Which three CLI commands are required if the guest WLAN is on WLAN 2? (Choose three.)

- A. config wlan security web-auth enable 2
- B. config wlan custom-web global enable 2
- C. config wlan custom-web webauth-type customized 2
- D. config wlan custom-web login-page login.html 2
- E. config wlan custom-web webauth-type internal 2
- F. config wlan custom-web login-page customized 2

**Answer: ACD**

### QUESTION 4

An engineer creating a configuration file to upload to a controller would like the guest WLAN to be set for L3 authentication only. What command must be included in the configuration file?

- A. config wlan security web-auth enable 2
- B. config wlan security wpa wpa2 disable 2
- C. config wlan security web-auth server-precedence 2 local radius ldap
- D. config wlan custom-web global enable 2

**Answer: A**

### QUESTION 5

An engineer is configuring the anchor controller for a guest network. What setting in the guest WLAN can be different from the foreign controllers?

- A. VLAN
- B. radio policy
- C. QOS setting
- D. WLAN advanced settings

**Answer:** A

#### **QUESTION 6**

All users on one of the two guest WLANs are failing to connect after a configuration change was made to a controller. What is the cause of the outage?

- A. The interface or VLAN of the anchor controller and foreign controller no longer match.
- B. The configuration of the failing WLAN no longer matches the foreign controllers.
- C. The address of the NAC guest server has been changed.
- D. The DHCP server on the foreign controller was changed.

**Answer:** B

#### **QUESTION 7**

What three items can be found on the Wireless Control System PCI DSS Compliance Report? (Choose three.)

- A. all authentication and encryption violations
- B. all ACL violations and reports
- C. all IDS threats
- D. detailed association history for clients connected to the network
- E. all SSIDs not using Client Exclusion
- F. all access points that have rogue detection enabled

**Answer:** ACD

#### **QUESTION 8**

An engineer is segmenting WLAN traffic by security options after the client has received an IP address. Which two security options are possible? (Choose two.)

- A. web policy
- B. Cisco Key Integrity Protocol
- C. PSK
- D. 802.1x
- E. VPN pass-through

**Answer:** AE

#### **QUESTION 9**

An engineer is configuring 802.1x authentication on an autonomous AP. What two configuration commands must be included on the AP if the RADIUS server IP is 10.9.4.9? (Choose two.)

- A. radius-server host 10.9.4.9 auth-port 1812 acct-port 1813 key Cisco123
- B. aaa new-model
- C. aaa authorization
- D. aaa attribute list 10.9.4.9
- E. aaa group server radius 10.9.4.9

**Answer:** AB

**QUESTION 10**

An engineer has configured passive fallback mode for RADIUS with default timer settings. What will occur when the primary RADIUS fails then recovers?

- A. RADIUS requests will be sent to the secondary RADIUS server until the secondary fails to respond.
- B. The controller will immediately revert back after it receives a RADIUS probe from the primary server.
- C. After the inactive time expires the controller will send RADIUS to the primary.
- D. Once RADIUS probe messages determine the primary controller is active the controller will revert back to the primary RADIUS.

**Answer:** C

**QUESTION 11**

What is the default SYSLOG level in a wireless LAN controller?

- A. alert
- B. notification
- C. error
- D. informational
- E. debugging

**Answer:** C

**QUESTION 12**

An engineer is configuring IDS signatures and sets Bcast deauth to enabled and immediately begins to see Broadcast deauthentication frame alerts.

What Cisco recommended solution would resolve this issue?

- A. disable Bcast deauth
- B. disable Broadcast SSID on the WLAN
- C. enable MFP on the WLAN
- D. locate and disable the attacker

**Answer:** C

## Thank You for Trying Our Product

### Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad.**
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER  
NETWORKS



EMC<sup>2</sup>  
where information lives®

**10% Discount Coupon Code: ASTR14**