

Vendor: Oracle

Exam Code: 1Z0-400

Exam Name: Oracle Communications Session Border

Controller Implementation Essentials

Version: DEMO

QUESTION 1

On a Net-Net 4500, a hardware-based timer will reset the system in the event of a catastrophic software or operating system failure.

This hardware timer is reset (preventing it from triggering) by the______

- A. Acme Control Protocol Daemon
- B. Border Element Redundancy Protocol Daemon (BERPD)
- C. Console-timeout/telnet-timeout configuration in system-config
- D. System clock
- E. Watchdog process

Answer: E

QUESTION 2

Which two are TRUE regarding the Net-Net 3820 and Net-Net 4500 Fan Module component?

- A. User-serviceable
- B. Self-cleaning
- C. Hot-swappable
- D. Redundant
- E. Liquid cooled

Answer: BE

QUESTION 3

To view an existing multiple-instance element's configuration you can go to the correct branch of the configuration tree and_____.

- A. Typeis -a.
- B. Enter the name of the element and then issue the show command.
- C. Type show ?and select from the displayed list.
- D. Type show <element name>.
- E. Select the element and then issue the show command.

Answer: D

QUESTION 4

Which two parameters are NOT phy-interface parameters?

- A. sub-port-id
- B. hostname
- C. name
- D. operation-type
- E. speed

Answer: BE

QUESTION 5

Which statements are TRUE about a Net-Net 4500 SIP interface?

- A. The SIP interface provides G.711 to G.729 transcoding functions ONLY when SIP is the signaling protocol.
- B. The SIP interface listens for SIP signaling on one or more configured IP address/port/transport combinations.
- C. You can only configure a single SIP port per realm.
- D. The SIP interface provides a service pipe to sipd, such that incoming signaling messages are presented to the SIP protocol daemon for processing.
- E. The SIP interface modifies headers, such as the TO and FROM, to provide topology hiding.

Answer: B

QUESTION 6

All of the following are components of the Session Border Controller's OS Media Control function, except:

- A. Quality of Service (QoS) Marking
- B. DTMF extraction (RFC2833)
- C. Dynamic Access Control
- D. Conferencing/Multipoint Control Unit (MTU) mixing
- E. Media supervision timers/call teardown

Answer: E

QUESTION 7

Which statement is FALSE about the sub-port-id field within a network-interface configuration?

- A. The value assigned to a sub-port-id field within a network-interface configuration element is globally unique within a Net-Net 4500's running configuration.
- B. The sub-port-id field has a range of 0-4095.
- C. The sub-port-id represents a VLAN tag value.
- D. The sub-port-id allows for multiple network-interface configuration elements to be bound to a single physical interface.
- E. Along with a network-interface configuration element's "name" field, comprises the primary key for the element.

Answer: D

QUESTION 8

_____is the percentage of a Session Border Controller's peer advertisement time for the other peer in the high availability (HA) pair to wait before considering the peer out of service.

- A. 2
- B. Percent-drift
- C. 3.1
- D. Standard-deviation-score
- E. State-field

Answer: B

Thank You for Trying Our Product

PassLeader Certification Exam Features:

- ★ More than 99,900 Satisfied Customers Worldwide.
- ★ Average 99.9% Success Rate.
- ★ Free Update to match latest and real exam scenarios.
- ★ Instant Download Access! No Setup required.
- ★ Questions & Answers are downloadable in PDF format and VCE test engine format.



- ★ Multi-Platform capabilities Windows, Laptop, Mac, Android, iPhone, iPod, iPad.
- ★ 100% Guaranteed Success or 100% Money Back Guarantee.
- ★ Fast, helpful support 24x7.

View list of all certification exams: http://www.passleader.com/all-products.html

























10% Discount Coupon Code: STNAR2014