



Vendor: Extreme Networks

Exam Code: EW0-200

Exam Name: Extreme Networks Associate (ENA)

Version: DEMO

QUESTION 1

Which of the following protocol filter/s is/are predefined in ExtremeWare?

- A. OSPF
- B. TCP
- C. NETBIOS
- D. All of these

Answer: C

QUESTION 2

Which command provides the following information?

Name	VID	Protocol	Addr	Flags	Proto	Super Ports
Default	0001	0.0.0.0	/BP	-----	ANY	8/ 16
MacVlanDis	4095	-----	-----	-----	ANY	0/ 0
Mgmt	4094	-----	-----	-----	ANY	0/ 1

```
Flags : M=ESRP Master, E=ESRP Slave, G=GVRP Enabled, L=Loopback Enabled
S=SuperVlan, s=SubVlan, R=SubVLAN IP Range Configured
C=Domain-masterVlan, c=Domain-memberVlan
f=IP Forwarding Enabled, m=IPmc Forwarding Enabled
r=RIP Enabled, o=OSPF Enabled, p=PIM Enabled, d=DVMRP Enabled
X=IPX RIP Enabled, P=IPX SAP Enabled
N=GNS Reply Enabled, Z=IPX Type 20 Forwarding Enabled
```

Answer: SHOW VLAN

QUESTION 3

Which statement is true? In a PC, the configured default gateway:

- A. Is always within the PC IP (sub) network.
- B. Is always outside the PC IP (sub) network.
- C. Is always behind a router.
- D. Can be anywhere.

Answer: A

QUESTION 4

This type of OSPF router has its router interfaces connected into multiple OSPF areas.

- A. ASBR.
- B. ABR.
- C. DR.
- D. BDR.

Answer: B

QUESTION 5

Which CLI command would you use to configure the switch to ignore STP for selected VLANs?

- A. enable ignore-stp vlan <stpd>
- B. enable ignore-bpdu stpd <stpd> vlan <vlan>
- C. enable ignore-bpdu stpd <stpd>
- D. enable ignore-stp vlan <vlan>

Answer: D

QUESTION 6

Which of the following CLI commands would you use to enable ECMP for RIP?

- A. enable rip route sharing
- B. enable route sharing rip
- C. enable iproute sharing
- D. None of these, ecmp is not supported by RIP

Answer: D

QUESTION 7

If you wish to silently drop all traffic destined for IP network 100.219.10.0/24 with a gateway of 10.219.10.1/24 and without receiving any ICMP messages that would otherwise be generated, which CLI command would you execute?

- A. configure iproute delete 100.219.10.0/24 gateway 10.219.10.1
- B. configure iproute default 100.219.10.0/24
- C. configure iproute add blackhole 100.219.10.0/24 gateway 10.219.10.1
- D. configure iproute add blackhole 100.219.10.0/24

Answer: D

QUESTION 8

What is true when VLAN corporate shows a protocol field with the value of NONE.

- A. VLAN corporate will not forward any traffic.
- B. VLAN corporate must be a MAC-based VLAN.
- C. It is not possible for a VLAN to have NONE listed as the protocol.
- D. None of these.

Answer: A

QUESTION 9

RIP is a routing protocol that scales to a limit. What is the maximum number of supported hop counts?

- A. 10
- B. 15
- C. 20
- D. 30

Answer: B

QUESTION 10

In order to span multiple VLANs across Extreme switches, the protocol EDP must be enabled.

- A. TRUE
- B. FALSE

Answer: B

QUESTION 11

After using the disable web command you later issue the show session command and see the following: How was it possible for someone to login with ExtremeWare Vista?

#	Login Time	User	Type	Auth	CLI Auth	Location
*	0 Thu Feb 28 14:07:18 2002	admin	console	local	disabled	serial
*	4 Thu Feb 28 17:43:36 2002	admin	http	local	disabled	10.0.5.100

- A. Admin level accounts can always login through console, telnet, and HTTP.
- B. You did not reboot after issuing the DISABLE WEB command.
- C. You did not save the configuration after issuing the DISABLE WEB command.
- D. The disable web command does not exist.

Answer: B

QUESTION 12

What information will the CLI Command how edp?provide?

- A. The EDP status of the local switch ports.
- B. The configured system names, Port numbers and VLANs of the remote Extreme switches
- C. The MAC address of the remote systems connected.
- D. All of the above

Answer: D

QUESTION 13

What is the maximum number of simultaneously active protocol filters in the switch for all ?based Extreme switch products?

- A. 7
- B. 14
- C. 15
- D. None of these

Answer: C