

Exam Code: 2B0-020

Exam Name: ES NetSight Atlas

Vendor: Enterasys Networks

Version: DEMO

Part: A

1: Which of the following device communication methods is used by MIB Tools?

- A.SNMPv1
- B.SNMPv3 Credential
- C.SNMPv3 Profile
- D.Max Access/Super User
- E.All of the above
- F.A and C only

Correct Answers: E

2: Which of the following definition(s) best describes the difference between managers and agents in SNMPv1 and SNMPv3?

- A.In SNMPv1, the manager and agent were distinctly different but performed overlapping functions. Managers resided on workstations; agents on remote devices.
- B.In SNMPv3, a distributed interacting collection of SNMP entities can reside on both management workstations and remote devices. Because each entity implements a portion of SNMP capability, an entity can act as an agent, a manager, or a combination of the two.
- C.In SNMPv1, the manager and agent were distinctly different and performed discrete functions: the manager ran applications; the agent provided functionality. Managers resided on workstations; agents on remote devices.
- D.A and B
- E.B and C
- F.All of the above

Correct Answers: E

3: A MIB not supported on all devices should be assigned to which SNMP Request Group, when defining a FlexView?

- A.Group 1
- B.Group 2
- C.Group 3
- D.Group 4
- E.All of the above
- F.B or C only

Correct Answers: F

4: What are the three predefined groups in Inventory Manager Network Elements?

- A.Chassis, Device Type and IP
- B.Chassis, Matrix and X-Pedition
- C.Matrix, SmartSwitch and X-Pedition
- D.Matrix, X-Pedition and IP

Correct Answers: A

5: How can network masks be displayed in CIDR notation in Router Services Manager?

- A.By selecting CIDR in the Network Mask option of Tools > Options
- B.By selecting CIDR in the device properties window
- C.By selecting Dot Delimited in the Display option of Tools > Options
- D.It is not possible to have network masks displayed in CIDR notation

Correct Answers: A

6: The MIB Tools Utility allows you to do all of the following, EXCEPT

- A.View object definitions
- B.Set object values
- C.Change IP addresses on devices
- D.Search for objects
- E.Browse the MIB database

Correct Answers: C

7: Which of the following statements are true about FlexViews?

- A.You can use the FlexView editor to define as many FlexViews as you want.
- B.You can create custom tabs to display desired MIB information.
- C.The FlexView Wizard is not available with Atlas Lite.
- D.All of the above
- E.A and C only

Correct Answers: D

8: What is the name of the file that defines the absolute path to your NetSight Plug-In applications?

- A.PlugIn.details
- B.common
- C.NetSight.properties
- D.Atlas.config

Correct Answers: C

9: The relationship among remote devices in each map is automatically generated by Console when you click the Retrieve button.

- A.True
- B.False

Correct Answers: B

10: What are the three tabs in the left panel of Inventory Manager?

- A.Devices, Traps, Archives
- B.Network Elements, Firmware Management, Configuration Management
- C.Details View, Archives, Chassis
- D.Properties, VLAN, Compass

Correct Answers: B

11: Which service must be stopped to modify the bootptab file?

- A.TFTP
- B.SNMP trapd
- C.Bootp
- D.All of the above

Correct Answers: C

12: Which Compass search type is used to locate authenticated users in a User Personalized Network?

- A.IP Address
- B.IP Subnet
- C.MAC Address
- D.User Name

Correct Answers: D

13: How many default Alarm & Events tables are available with the initial installation of Atlas Console?

- A.One
- B.Two
- C.Three
- D.Four

Correct Answers: B

14: Within the context of NetSight Atlas Policy Manager, which of the following statements describe a Role?

- A.A VLAN membership
- B.A defined function within the business organization
- C.A traffic description and associated action
- D.A classification rule

Correct Answers: B

15: What step should be taken after editing or deleting a redundant rule?

- A.Click the Re-evaluate Reference Index button to seek additional redundancies to the Reference rule
- B.Click the Advance Reference Index button to start a new search
- C.Click the Close button to exit the Find Redundant Rules window
- D.No action is necessary

Correct Answers: A

16: Device Manager provides all of the following, EXCEPT

- A.Graphic representation of a device
- B.Configuration file upload/download

- C. System level configuration
- D. Broadcast Suppression configuration

Correct Answers: C

17: With SNMPv3, the source is authenticated

- A. to prevent disclosure of sensitive information while en route
- B. to make sure the user has permission to access the device
- C. to verify the message was not modified en route
- D. to read or to modify subsets of the target data
- E. Both A and C

Correct Answers: B

18: The Firmware Upgrade Wizard allows you to enter a reset delay time for devices that support timed reset. How can you reset devices that do not support timed reset?

- A. You cannot reset devices that do not support timed reset.
- B. After selecting the devices in the table, click Start to initiate manual resets.
- C. It is necessary to walk to the device to initiate a reset.
- D. After closing the Firmware Upgrade Wizard, you open the Manual Device Reset Wizard.

Correct Answers: B

19: What directory contains the NetSight Atlas background services on Unix?

- A. /usr/bin
- B. /etc/rc2.d
- C. /usr/local/Enterasys Networks/NetSight Atlas Console/bin
- D. /usr/sbin

Correct Answers: B

20: What benefits are gained with SNMPv3?

- A. Better error codes
- B. Encrypted messages
- C. Fast table retrieval
- D. All of the above

Correct Answers: D