

Exam Code: NS0-920

Exam Name: Network Appliance NetCache Deployment
Options and Streaming

Vendor: Network Appliance

Version: DEMO

Part: A

1: What version(s) of SSH does NetCache support?

- A. Versions 1 and 2
- B. Version 2 only
- C. Versions 2 and 3
- D. Version 3 only
- E. None

Correct Answers: A

2: Which set of acceleration rules will best allow for acceleration of a Windows Media Server that uses MMS and HTTP for transport protocols?

NetCache IP: 10.1.2.3 netcache.server.com

Streaming Server IP: 10.1.2.5 m.server.com

- A. streaming.acceleration.rules=\n10.1.2.3 1755 * * 10.1.2.5 1755 m.server.com *\n10.1.2.3 80 * * 10.1.2.5 80 m.server\n\n
- B. config.streaming.acceleration.rules=\n10.1.2.3 1755 * * 10.1.2.5 1755 m.server.com *\n\nconfig.http.acceleration.rules=\n10.1.2.3 80 * * 10.1.2.5 80 m.server.com *\n\n
- C. config.acceleration.rules=\nmms 10.1.2.3 10.1.2.5 netcache.server.com m.server.com\nhttp 10.1.2.3 10.1.2.5 netcache.server.com m.server.com\n\n
- D. config.streaming.acceleration.rules=\n10.1.2.3 554 * * 10.1.2.5 554 m.server.com *\n10.1.2.3 80 * * 10.1.2.5 80 m.server.com *\n\n

Correct Answers: A

3: What happens if you assign a service group ID of 4 on one NetCache appliance, and you assign a service group ID of 2 on another NetCache appliance?

- A. The two groups will load balance between each other.
- B. The WCCP router will automatically group the two together.
- C. Each NetCache appliance will join a different service group.
- D. The NetCache appliances use only the ID assignment for internal information, so there is no effect.

Correct Answers: C

4: Which three are true about WCCP? (Choose 3)

- A. WCCP service groups must support a single protocol.
- B. WCCP service groups can consist of one or more routers or proxy-cache servers.
- C. WCCP service groups must be defined with the same settings.
- D. Traffic redirection and distribution are based on logical WCCP service groups.

Correct Answers: B C D

5: What is the purpose of the "Here I Am" message?

- A. It identifies the NetCache appliance as the router.
- B. It identifies the service group membership.
- C. It announces that the NetCache appliance is available after a shutdown.
- D. It identifies that the NetCache appliance has received a request.

Correct Answers: B

6: When traffic is tunneled, the NetCache appliance can take which two actions? (Choose 2)

- A. It can be used with manually configured browsers.
- B. It passes specified types of nonstandard traffic through without caching it.
- C. It examines the source and destination information, and caches the resulting objects.
- D. It receives requests and allows or denies based on ACLs.

Correct Answers: B D

7: When is information recorded into the Streaming Access log?

- A. When the client streaming connection is opened.
- B. Within 500 ms of connect.
- C. Throughout the streaming session.
- D. When the client streaming connection is closed.

Correct Answers: D

8: When you have a Digital Rights Management (DRM) streaming, authentication is performed between which two devices?

- A. HTTP server and client player
- B. streaming media server and client player
- C. authentication server and router
- D. domain controller and streaming media server

Correct Answers: B

9: A list of HTTP headers returned to a client for a cache hit on a stream may be viewed using the _____.

- A. smstats command
- B. sysstat command
- C. Streaming Details log
- D. object command

Correct Answers: D

10: Bandwidth allocation rules can be used to optimize streaming performance in which three

ways? (Choose 3)

- A.They can allocate bandwidth by user and group.
- B.They can manage NetCache bandwidth utilization to ensure bandwidth for other uses.
- C.They can allocate bandwidth based on CPU and memory usage.
- D.They can restrict or deny connections.

Correct Answers: A B D

11: Which statement about a Layer 4 switch is true? (Choose 3)

- A.It can be configured to pass non-HTTP traffic directly to the Web.
- B.It passes traffic based on the port number in a TCP/IP packet.
- C.It passes traffic based on the URL of the client's request.
- D.It uses MAC address rewriting to redirect packets.

Correct Answers: A B D

12: Request forwarding is useful for doing which of the following?

- A.To process URLs that are not cacheable, or for sites that use IP authentication.
- B.To force all traffic through the NetCache appliance.
- C.To create a load balancing scheme.
- D.To allow the NetCache to send the URL request as if it is coming from the cache and not the client.

Correct Answers: A

13: Why must a Layer 4 switch be on the same subnet as the NetCache appliance?

- A.To use IP-GRE encapsulation.
- B.To prevent IP spoofing.
- C.To use MAC address rewriting.
- D.To monitor the health of the NetCache appliance.

Correct Answers: C

14: How will the following configuration command affect the factory default configuration?
set config.http.transparency on

- A.NetCache starts listening promiscuously on port 80.
- B.NetCache stops listening on port 3128 and restarts listening promiscuously on port 3128.
- C.An error message is reported; no configuration change occurs.
- D.An error message is reported; NetCache starts listening promiscuously on all TCP ports.

Correct Answers: B

15: Which can be determined about an .ASF object by using the object command?

- A.The playing time of the stream.
- B.The amount of disk space used to store it on the cache.
- C.The number of packets in the stream.
- D.The author of the stream.

Correct Answers: C