Vendor: HP

Exam Code: HP2-Z19

Exam Name: Implementing HP Network Security Solutions

Version: DEMO

QUESTION 1
Which E-Series CLI commands enable you to view all show commands available in the current context? (Select two.)

A. Switch# show /?
B. Switch# show all
C. Switch# show help
D. Switch# show ?
E. Switch# show <tab>
F. Switch# help show

Answer: DE

QUESTION 2
You are at the manager level prompt in the CLI of an HP E3500 yl switch. Which options are available at this prompt? (Select two.)

A. assign IP address to VLAN interface
B. enable IP routing
C. restart the switch
D. disable ports
E. update software

Answer: CE

QUESTION 3
Which HP E-Series switch models display the following prompt in the interface configuration context? (Select two.)HP Switch(eth-A24)#

A. E8212 zl
B. E6600-24G
C. E5412-96G zl
D. E2910-24G al
E. E3500-48G-POE yl

Answer: ABE

QUESTION 4
You make configuration changes to the running configuration of your HP E3500 yl switch. Which command saves these changes to your startup configuration?

A. save running-config
B. copy running-config startup-config
C. write memory
D. write config

Answer: C

QUESTION 5

You must update the software on an HP E3500 yl switch. Which devices can be sources for the copy command? (Select two.)

A. USB flash drive
B. management workstation hard drive
C. TFTP server
D. FTP server
E. Compact Flash card

Answer: AC

QUESTION 6
Refer to the exhibit below.

```
hostname "E5406"
module 1 type J8702A
vlan 1
    name "DEFAULT_VLAN"
    untagged A9-A24
    ip address 192.168.1.1 255.255.255.0
    no untagged A1-A8
    exit
vlan 5
    name "VLAN5"
    untagged A1-A4
    ip helper-address 192.168.1.2
    ip address 192.168.5.1 255.255.255.0
    exit
vlan 6
    name "VLAN6"
    untagged A5-A8
    ip helper-address 192.168.1.2
    ip address 192.168.6.1 255.255.255.0
    exit
vlan 2
    name "VLAN2"
    ip address 192.168.2.1 255.255.255.0
    exit
snmp-server community "public" unrestricted
spanning-tree
spanning-tree priority 0
```

You have configured IP helper addresses for VLAN 5 and VLAN 6 on this HP E5406 zl switch. However, users in these VLANs report that their computers are not receiving DHCP addresses. Which feature must be enabled to address this problem?

A. DNS
B. DHCP relay
C. IP routing
D. DHCP snooping

Answer: B

QUESTION 7
Refer to the exhibit below.

```
E5406# show vlan 100

 Status and Counters - VLAN Information - VLAN 100

   VLAN ID : 100
   Name  : VLAN100
   Status : Port-based
   Voice : No
   Jumbo : No

   Port Information Mode      Unknown VLAN Status
   --------------- --------   ------------ ----------
   A24             Untagged   Learn        Up

E5406# show vlans port a24

 Status and Counters - VLAN Information - for ports A24

   VLAN ID Name                                     | Status     Voice Jumbo
   ------- ---------------------------------------- + ---------- ----- -----
   100     VLAN100                                  | Port-based No    No
```

You enter the following command at the switch ̄s CLI: E5406(vl a-100)# no untag a24 Why does this command fail?

A. Port A24 is not a member of VLAN 100.
B. Port A24 must be a member of at least one VLAN.
C. VLAN 100 must have at least one port member.
D. no untag a24 is an invalid CLI command.

Answer: B

QUESTION 8
Which security technology requires that you set read/write community names?

A. SFTP
B. SSH
C. SNMP
D. HTTPS
E. SMTP

Answer: C

QUESTION 9
What are benefits of implementing Secure Socket Shell (SSH) for remote management of HP switches? (Select two.)

A. user accounting
B. encryption of management traffic
C. stronger passwords
D. enforcement of management VLAN
E. secure authentication
F. encryption of all traffic

Answer: BE

QUESTION 10
Which remote management interface on an E-Series switch can be secured by enabling Secure Sockets Layer (SSL)?

A. console
B. menu
C. web management
D. Telnet

Answer: C

QUESTION 11
What is the effect of the following commands entered at the CLI of an HP E8212 zl switch with routing and RIP enabled?E8212(rip)# redistribute ospf

A. The switch will filter OSPF routes from RIP updates received from peers.
B. The switch will include routes learned through OSPF in all RIP updates.
C. The switch will include routes learned through RIP in all OSPF link-state messages.
D. The switch will give preference to OSPF routes over RIP routes in its route table.

Answer: B

QUESTION 12
Refer to the exhibit below.

```
                   IP Route Entries
Destination        Gateway        VLAN Type      Sub-Type   Metric   Dist.
-----------------  ------------   ---- --------   ---------  -------  -----
 127.0.0.0/8       reject              static                 0        0
```

What is indicated by this entry in the IP route table of an HP E8212 zl switch?

A. The switch has been configured with an ACL that blocks communications with the loopback interfaces.
B. The switch does not permit communications with any loopback interface.
C. Traffic to this interface is rejected with the single exception of traffic to the host address of the switch ̅s loopback interface (127.0.0.1/ 32).
D. A loopback interface is configured with 127.0.0.0.

Answer: C

Thank You for Trying Our Product

PassLeader Certification Exam Features:

★ More than 99,900 Satisfied Customers Worldwide.

★ Average 99.9% Success Rate.

★ Free Update to match latest and real exam scenarios.

★ Instant Download Access! No Setup required.

★ Questions & Answers are downloadable in PDF format and VCE test engine format.

★ Multi-Platform capabilities - Windows, Laptop, Mac, Android, iPhone, iPod, iPad.

★ 100% Guaranteed Success or 100% Money Back Guarantee.

★ Fast, helpful support 24x7.

View list of all certification exams: http://www.passleader.com/all-products.html

10% Discount Coupon Code: STNAR2014