



**Vendor:** IBM

**Exam Code:** C4120-783

**Exam Name:** IBM PureFlex Technical Support V2

**Version:** DEMO

**QUESTION 1**

How are the management networks of two PureFlex chassis interconnected?

- A. CMM external ports
- B. Interconnect nodes
- C. Front and rear flex cables
- D. Top of rack InfiniBand switch

**Answer:** A

**QUESTION 2**

A customer has a legacy x86 deployment on physical servers. What benefit does VMware offer to preserve legacy workloads?

- A. Allows use of Active Memory Expansion in VMware
- B. Allows use of IBM Storage Management Console for VMware vCenter plug-in
- C. User-controlled CPU frequencies allow slower legacy hardware timings to be preserved
- D. Select operating systems not natively supported on the new hardware are supported under VMware

**Answer:** D

**QUESTION 3**

How are the management networks of two PureFlex chassis interconnected?

- A. Interconnect nodes
- B. CMM external ports
- C. Front and rear flex cables
- D. Top of rack InfiniBand switch

**Answer:** C

**QUESTION 4**

A PureFlex technical specialist is discussing the PureFlex family with a prospective customer. They are concerned about available chassis space. Which PureFlex compute node option is full width?

- A. x240
- B. p260
- C. x220
- D. p460

**Answer:** D

**QUESTION 5**

A customer is considering a PureFlex Standard solution. Which of the following is included in the five day IBM Lab Services engagement?

- A. Demonstrate Live Application Mobility

- B. Implement System Server Pools with VMControl
- C. Create an image repository for use with VMControl
- D. Use vCenter to create a cluster of virtual servers

**Answer: C**

**QUESTION 6**

Each x86 node can be individually connected to a portable console, keyboard, and mouse. This is often referred to as "crash cart" management capability. Which of the following is required to perform this connection?

- A. Physically plugging a KVM cable to the CMM
- B. Physically plugging in a console breakout cable to the compute node
- C. Physically plugging in a serial cable to the diagnostic port of the CMM
- D. Physically plugging in a proprietary male 9 pin cable to the compute node

**Answer: B**

**QUESTION 7**

A customer has an application which requires access to more than two separate networks and has a limited number of physical ports to support the environment. They plan on implementing Virtual NIC interface. Which of the following meets these requirements?

- A. 802.1Q relies on data center bridging
- B. 802.1Q allows for NIC teaming providing additional ports
- C. 802.1Q controls the quality of service which can be used to prioritize traffic to those applications
- D. 802.1Q VLAN tagging is used to divide one physical Ethernet interface into several logical interfaces that belong to different VLANs

**Answer: D**

## Thank You for Trying Our Product

### PassLeader Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad.**
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.passleader.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER  
NETWORKS



EMC<sup>2</sup>  
where information lives®

**10% Discount Coupon Code: STNAR2014**