

Exam Code: HP0-A01

Exam Name: HP-UX 11i v3 System Administration

Vendor: HP

Version: DEMO

Part: A

1: What does the linkloop command test?

- A.router activity
- B.Maximum Transmission Unit (MTU) size
- C.MAC address connectivity between network cards
- D.loopback address connectivity between network cards

Correct Answers: C

2: Which file contains the information sent in response to a bootp request?

- A./etc/services
- B./etc/bootptab
- C./etc/inetd.conf
- D./etc/bootp.conf

Correct Answers: B

3: Which commands can confirm host name resolution (DNS/Bind) is working correctly?

- A.whois
- B.uname
- C.nsquery
- D.hostname
- E.gethostbyname

Correct Answers: C

4: What is IP multiplexing on a UNIX host?

- A.increasing throughput on the network interface
- B.binding the same IP address to multiple network interface
- C.binding more than one IP address to a single network interface
- D.binding more than one MAC address to a single network interface

Correct Answers: C

5: Which tools have been deprecated with the introduction of the nwmgr command? (Select three.)

- A.netstat
- B.ifconfig
- C.linkloop
- D.lanscan
- E.lanadmin

Correct Answers: C D E

6: How can you enable only NFS version 4 support on HP-UX 11i v3?

- A.HP-UX v3 does not support NFSv4.
- B.Change the NFSv4 kernel parameter to yes, recompile the kernel and reboot.
- C.Using only NFSv4 is not supported; NFSv2 and NFSv3 are always enabled.
- D.Set the configuration parameters NFS_SERVER_VERSMIN and NFS_SERVER_VERSMAX

to 4.

Correct Answers: D

7: Which NFS server file contains a list of clients that currently have the server's NFS file systems mounted?

- A./etc/fstab
- B./etc/rmtab
- C./etc/nfstab
- D./etc/mnttab
- E./etc/exports

Correct Answers: B

8: What is the length of an IPv4 address?

- A.32 bits
- B.48 bits
- C.64 bits
- D.128 bits

Correct Answers: A

9: What are the major features of IPFilter on HP-UX 11i v3? (Select three.)

- A.creates extensive logs
- B.supports X.25 Interfaces
- C.installed and enabled by default
- D.provides a new GUI configuration tool
- E.supports Network Address Translation (NAT)

Correct Answers: A B E

10: Which command displays Internet to Ethernet address resolution?

- A.arp
- B.lanscan
- C.ifconfig
- D.traceroute

Correct Answers: A

11: What are the new features offered in NFS version 4? (Select three.)

- A.integrated security
- B.asynchronous write support
- C.integrated file locking support
- D.simplified firewall configuration
- E.support for the UDP network transport

Correct Answers: A C D

12: Which feature of HP CIFS allows a Unix uid or gid to be mapped to a Windows account or group?

- A.nmbd
- B.smbd
- C.winbind
- D.smbclient

Correct Answers: C

13: Click the Task button.

Using drag and drop, match each network configuration file with its common definition.

Match the network configuration files with their intended use.

place here	Contains DNS client configuration information
place here	Defines databases to be used and search order for aliases, password, hosts, etc.
place here	Used for permission checking when executing remote mounts, remote logins, and
place here	Associates Internet (IP) addresses with official network names and aliases.

Correct Answers:

Match the network configuration files with their intended use.

<i>/etc/resolv.conf</i>	Contains DNS client configuration information
<i>/etc/nsswitch.conf</i>	Defines databases to be used and search order for aliases, password, hosts, etc.
<i>/etc/netgroup</i>	Used for permission checking when executing remote mounts, remote logins, and
<i>/etc/networks</i>	Associates Internet (IP) addresses with official network names and aliases.

14: Which file contains the modified configuration values that will be used the next time the cimserver starts?

- A.cimserver.conf

- B.cimserver_start.conf
- C.cimserver_planned.conf
- D.cimserver_nextboot.conf

Correct Answers: C

15: Which pair of statements is true when launching a tool using HP System Insight Manager (HP SIM)?

- A.- authorizations are configured in HP SIM
 - users are authenticated using PAM on the HP SIM Server
- B.- authorizations are configured in HP SIM
 - users are authenticated using HP SIM's internal user database
- C.- authorizations are configured in Select Access
 - users are authenticated using HP SIM's internal user database
- D.- authorizations are derived from operating system login account permissions
 - users are authenticated using PAM on the HP SIM Server

Correct Answers: A