



Vendor: Citrix

Exam Code: 1Y0-240

Exam Name: Citrix NetScaler Essentials and Traffic Management

Version: DEMO

QUESTION 1

Scenario: A Citrix Administrator has configured the following Access Control List (ACL) to block traffic from the IP address 10.102.29.5.

add simpleacl rule1 DENY -srcIP 10.102.29.5

A week later, the administrator found that the ACL is no longer present on the NetScaler.

What could be the reason for this?

- A. The administrator did NOT run the apply ACL command.
- B. The NetScaler has been restarted without saving the configurations.
- C. The Simple ACLs remain active for only 600 seconds.
- D. The Simple ACLs remain active for only 60 seconds.

Answer: A

QUESTION 2

Which scenario will cause automatic high availability (HA) synchronization to fail?

- A. Different build versions
- B. Manually forced synchronization
- C. A force failover
- D. A configuration change to the primary NetScaler

Answer: B

QUESTION 3

Scenario: A Citrix Administrator is concerned about the amount of health checks the NetScaler is sending to the backend resources. The administrator would like to find a way to remove health checks from specific bound services.

How can the administrator accomplish this?

- A. Use the No-Monitor option.
- B. Use Service Groups to minimize health checks.
- C. Unbind the current monitor.
- D. Use reverse condition monitoring.

Answer: A

QUESTION 4

Scenario: A Citrix Administrator needs to add 10 new web servers to an existing server farm. The new servers are configured to serve the same applications and connections and are twice the capacity of the existing servers. The administrator wants to ensure that they are being fully utilized. Currently in the environment, the default load-balancing method is being used.

To ensure that only the 10 new servers are receiving twice the connections of the old servers without changing the load balancing to the rest of the environment, the administrator needs to add a weight of _____ to the services attached to the _____ servers. (Choose the correct option to complete the sentence.)

- A. 50; new
- B. 50; old
- C. 2; new

D. 2; old

Answer: CD

QUESTION 5

A Citrix Administrator has executed the commands in the screenshot on the NetScaler using the command-line interface.

View the screenshot (Exhibit).



```
>  
> add transform profile prof_url_change  
Done  
> add transform action "URL change" prof_url_change 10  
Done  
> set transform action "URL change" -priority 10 -reqUrlFrom "https://*" -reqUrlInto "http://*" -resUrlFrom "http://*" -resUrlInto "https://*" -priority 10  
Done  
> add transform policy pol_url_change true prof_url_change  
Done  
> bind lb vserver LB_vserver -policyName pol_url_change -priority 100 -gotoPriorityExpression END -type REQUEST
```

Which two replacements will be the outcome of executing these commands? (Choose two.)

- A. http:// will be replaced by https:// in the HTTP RESPONSE
- B. https:// will be replaced by http:// in the HTTP RESPONSE
- C. http:// will be replaced by https:// in the HTTP REQUEST
- D. https:// will be replaced by http:// in the HTTP REQUEST

Answer: B

QUESTION 6

What is the effect of the set cmp parameter -cmpBypassPct 70 command if compression is enabled on the NetScaler?

- A. Compression will be bypassed if the NetScaler bandwidth consumption is more than 70%.
- B. Compression will be bypassed if the NetScaler CPU load is 70%.
- C. Compression will be bypassed if the NetScaler bandwidth consumption is less than 70%.
- D. Compression will be bypassed if the NetScaler Memory utilization is 70%.

Answer: B

QUESTION 7

A Citrix Administrator needs to configure the Lights Out Management (LOM) port. Which statement is applicable to LOM?

- A. LOM is accessed using Command-Line Interface (CLI).
- B. LOM IP address should be in the same subnet as NSIP.
- C. LOM firmware is included in the NetScaler upgrade package.
- D. LOM port can be used to remotely monitor and manage the appliance.

Answer: A

QUESTION 8

Scenario; A Citrix Administrator would like to grant access to a Junior Administrator on the NetScaler. The administrator would like to grant full access to everything except the following:

- * Shell Access
- * User Configuration access
- * Partition Configuration access

Which pre-existing command policy would meet the needs of the scenario?

- A. Superuser
- B. Network
- C. Operator
- D. Sysadmin

Answer: A

QUESTION 9

A Citrix Administrator notices that the NetScaler is sending the IP addresses of all the active services in the DNS response.

The administrator can use the set gslb vserver<name>_____parameter to avoid this behavior. (Choose the correct option to complete the sentence.)

- A. EDR DISABLED
- B. EDR ENABLED
- C. MIR ENABLED
- D. MIR DISABLED

Answer: CD

QUESTION 10

What is the effect of the set gslb parameter - GSLBSvcStateDelayTime 10 command on the Global Server Load Balancing (GSLB) environment, when Metric Exchange Protocol (MEP) is enabled?

- A. The Metric Exchange Protocol (MEP) will be marked as DOWN if the GSLB service has been DOWN for 10 seconds.
- B. The Metric Exchange Protocol (MEP) will be marked as DOWN if the GSLB vServer has been DOWN for 10 seconds.
- C. The GSLB services will be marked as DOWN, if the Metric Exchange Protocol (MEP) connection has been DOWN for 10 seconds.
- D. The GSLB services will be marked as DOWN if the service has been DOWN for 10 seconds.

Answer: C

Thank You for Trying Our Product

PassLeader Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.passleader.com/all-products.html>



10% Discount Coupon Code: STNAR2014