

Vendor: IBM

**Exam Code:** C1000-002

**Exam Name:** IBM MQ V9.0 System Administration

Version: DEMO

#### **QUESTION 1**

After completing an IBM MQ for z/OS installation and customization, how can a successful installation be verified?

- A. Review the z/OS MQ SMF records.
- B. Run the command runmqsc -installation\_verify.
- C. Put a test message on a newly created z/OS queue.
- D. Use the MQ for z/OS installation verification programs (IVPs).

## Answer: D Explanation:

https://www.ibm.com/support/knowledgecenter/en/SSFKSJ\_9.1.0/com.ibm.mq.ins.doc/q009680\_. htm

#### **QUESTION 2**

For MQ Advanced for distributed platforms, which two components are included? (Select two.)

- A. MQ Appliance
- B. Managed File Transfer
- C. MessageSight
- D. IBM MQ Internet Pass-Thru
- E. Advanced Message Security

#### Answer: BE Explanation:

https://www.ibm.com/support/knowledgecenter/en/SSFKSJ\_7.5.0/com.ibm.mq.pro.doc/q126140\_.htm

#### **QUESTION 3**

An administrator is asked to forward all messages to queue `TEST.TEMP' if the messages destined for `TEST.LOCAL' end up on the dead letter queue.

Which rule in the dead letter handler rules table will enable the administrator to achieve this objective?

- A. REASON(MQRC\_Q\_FULL) ACTION(FWD) FWDQ(&DESTQ) HEADER(NO)
- B. REASON(\*) ACTION(FWD) FWDQ(`TEST.TEMP') HEADER(NO) DESTQ(`TEST.LOCAL')
- C. REASON(\*) ACTION(RETRY) FWDQ(`TEST.LOCAL') HEADER(NO) INPUTQ(`TEST.TEMP')
- D. REASON(MQRC\_Q\_FULL) ACTION(IGNORE) FWDQ(`TEST.TEMP') HEADER(NO) DESTQ (`TEST.LOCAL')

Answer: B

#### **QUESTION 4**

What is the purpose of the -s secretText parameter used in the prepareha and crthagrp commands on MQ Appliance?

- A. To be used as the unique key for the appliances.
- B. To be used to decide. In secret, which appliance will be the preferred appliance.
- C. To generate a short-lived password used to create two keys, one for each appliance.
- D. To generate a short-lived password used to set up on unique key for the appliances.

### Answer: A Explanation:

https://www.ibm.com/support/knowledgecenter/en/SS5K6E\_9.0.0/com.ibm.mqa.doc/reference/H Acmd/crthagrp.htm

#### **QUESTION 5**

Which channel may be configured with a channel auto-definition exit?

- A. Sender Channel
- B. Receiver Channel
- C. Requester Channel
- D. Client-Connection Channel

### Answer: A Explanation:

https://www.ibm.com/support/knowledgecenter/en/SSFKSJ\_9.0.0/com.ibm.mq.con.doc/q017240\_.htm

#### **QUESTION 6**

An administrator has been asked to make changes to MQ config so that the MQ client application APP\_A connecting to queue manager QM1 can reconnect automatically without re-starting the applications. What does the administrator need to configure to achieve this?

- A. Alter QMGR and set the attribute RECONN(YES)
- B. Alter SVRCONN channel and set attribute AUTOCONN(TRUE)
- C. Configure DefRecon attribute of CHANNELS stanza in mqclient.ini
- D. Configure AutoConnect attribute of CHANNELS stanza in mgclient.ini

Answer: C

#### **QUESTION 7**

A new LTS release of IBM MQ is made generally available. The versioning information is 9.0.0.0. When the next level of fixes is made available for this product what will the versioning information look like?

- A. 9.1.0.0
- B. 9.0.1.1
- C. 9.0.1.0
- D. 9.0.0.1

## Answer: D Explanation:

https://www.ibm.com/support/knowledgecenter/en/SSFKSJ\_9.0.0/com.ibm.mq.pla.doc/q004715\_. htm

#### **QUESTION 8**

An instance of IBM MQ on Unix regularly processes larger messages. Which condition will have a positive impact on message throughput given that the system is short of real memory?

- A. larger log buffer sizes
- B. Application processing outside of a unit of work
- C. Defining queue using large persistent queue buffers
- D. Defining queues using large non-persistent queue buffers

Answer: D

#### **QUESTION 9**

When configuring MQ shared queues on z/OS, where are the queue objects that represents the attributes of the shared queues held?

- A. VSAM database
- B. External SQL Server
- C. Shared DB2 repository
- D. Shared Oracle database

Answer: C

#### **QUESTION 10**

A failed MQ on z/OS request is received with a reason code `MQRC\_STORAGE\_MEDIUM\_FULL'. What are two reasons for this type of failure? (Select two.)

- A. Application are offline
- B. Cannot write to the disk
- C. The coupling facility is full
- D. Buffer pool has reached the limit
- E. There is not enough space remaining on the page set

Answer: CE

#### **QUESTION 11**

In application triggering what is the role of trigger monitor process?

- A. It monitors the initiation queue and based on trigger message issues a command to start an application.
- B. It monitors the transmission queue and based on trigger message issues a command to start an application.
- C. It monitors the application queue and when the trigger conditions are met and issues a command to start an application.
- D. It monitors the application queue and when the trigger conditions are met, it creates a message and puts it on initiation queue.

# Answer: A Explanation:

https://www.ibm.com/support/knowledgecenter/en/SSFKSJ\_9.0.0/com.ibm.mq.adm.doc/q021640 \_.htm

### **Thank You for Trying Our Product**

### **Passleader Certification Exam Features:**

- ★ More than 99,900 Satisfied Customers Worldwide.
- ★ Average 99.9% Success Rate.
- ★ Free Update to match latest and real exam scenarios.
- ★ Instant Download Access! No Setup required.
- ★ Questions & Answers are downloadable in PDF format and VCE test engine format.



- ★ Multi-Platform capabilities Windows, Laptop, Mac, Android, iPhone, iPod, iPad.
- ★ 100% Guaranteed Success or 100% Money Back Guarantee.
- ★ Fast, helpful support 24x7.

View list of all certification exams: <a href="http://www.passleader.com/all-products.html">http://www.passleader.com/all-products.html</a>

























10% Discount Coupon Code: ASTR14