



Vendor: Huawei

Exam Code: H11-861_V3.0

Exam Name: HCIP-Collaboration V3.0

Version: DEMO

QUESTION 1

In video conferencing, local noise is required not to be greater than ().

- A. 36dB
- B. 38dB
- C. 40dB
- D. 34dB

Answer: B

QUESTION 2

Common SIP calls the SDP negotiation process includes (). (3 answers).

- A. Invite with SDP, and then 2XX responds with SDP
- B. Invite with SDP, reliable 1XX response with SDP, and final 2XX response without SDP
- C. None with SDP
- D. Invite/Relinvite and Final Response (2XX) both come with SDP's processing

Answer: ABD

QUESTION 3

H.323 The last digit 3 in the protocol represents ().

- A. B-ISDN-based network
- B. Based on networks with quality of service assurance
- C. Networks based on packet transfer protocols
- D. GSTN- and wireless network

Answer: C

QUESTION 4

The envelope in the media streaming interconnection scheme is created by which of the following protocols is established. ()

- A. Q.931
- B. H.460.18
- C. H.460.19
- D. H.225.0

Answer: C

QUESTION 5

Hd terminal 3G network configuration, the following statement is correct ().

- A. To configure 3G network parameters requires the endpoint's License to support 3G networks
- B. The default IP setting for 3G parameters is static
- C. All 3G card HD terminals can be applied
- D. The APN in the 3G configuration parameters is used for all data card

Answer: A

QUESTION 6

In a networking network, the SETUP connection of the private network terminal is ().

- A. TS
- B. GK
- C. Public Terminal
- D. MCU

Answer: A

QUESTION 7

H.225 contains which of the following signalings (). (2 answers).

- A. Q.931
- B. H.281
- C. RAS
- D. T.120

Answer: AC

QUESTION 8

The response message is 3XX for ().

- A. The request was received, processed, and successfully accepted
- B. The request message has been received and is being processed
- C. Further action is required to complete the request
- D. Indicates that the SIP server failure could not complete the processing of the correct message

Answer: C

QUESTION 9

The following description of the cascading characteristics of the miniMCU is correct. () (3 answers).

- A. MiniMCU terminals support up to three cascading conferences
- B. Supports cascading conferencing in the primary miniMCU for conference control
- C. Supports H.323 cascade port calls in cascading conferencing
- D. Support for each terminal venue in a cascading conference to join the meeting as a SIP H323 call

Answer: BCD

QUESTION 10

The following socket on the MCU is the default service network port. ()

- A. GE0
- B. GE1

- C. FE
- D. RS232

Answer: A

QUESTION 11

Under static NAT networking, the signaling description of the public network terminal called the private network terminal is correctly (). (3 answers).

- A. The Caller CS Addr address is the NAT address of the private network terminal
- B. Callee CS addr is the NAT address
- C. The DST address is the NAT address of the private endpoint
- D. The DST address actually processed by the firewall is a private network address

Answer: BCD

QUESTION 12

The default operating mode of the GE1 port of the MCU is ().

- A. Ride the Wall
- B. Grab Package
- C. backup
- D. Dynamically switch

Answer: C

QUESTION 13

The H.460 protocol specifies that H.323 signaling parts of the public-private network traversal are handled. ()

- A. H.460.18
- B. H.460.19
- C. H.460.20
- D. H.460.21

Answer: A

QUESTION 14

Under static NAT networking, the SRC address of the terminal under the private network changes to ().

- A. No change
- B. Convert to NAT exit address
- C. Converts to any available public address
- D. Convert to GK address

Answer: B

QUESTION 15

In the Early state, the caller can terminate the dialog by sending (). (2 answers).

- A. BYE
- B. CANCEL
- C. UPDATE
- D. NOTIFY

Answer: AB

QUESTION 16

In the Early state, dialog can be terminated by (). (3 answers).

- A. The caller sends a BYE
- B. The caller sends CANCEL
- C. Called Failure Response
- D. Called to send BYE

Answer: ABC

QUESTION 17

In audio encoding, which of the following is a speech quality metric. () (3 answers).

- A. Packet loss rate
- B. Delay
- C. Band width
- D. Back-to-back

Answer: ABC

QUESTION 18

RAS performs management functions, mainly including :() (3 answers).

- A. enroll
- B. Access Control
- C. safe
- D. State

Answer: ABD

QUESTION 19

In 230.H.460 networking, what protocol does the tunnel between the terminal and the client GK follow? ()

- A. H.460
- B. H.323
- C. H.460.18/19
- D. Q.931

Answer: B

QUESTION 20

MCU In Wall Riding mode, () needs to be registered with GK.

- A. GE1 Port
- B. Both GE1 and GE0 can be
- C. FE ports
- D. GE0 Port

Answer: D

QUESTION 21

H.460 Signaling interoperability scheme ().

- A. The public network terminal adopts the H.460 protocol for communication
- B. The private network terminal uses the H.460 protocol to communicate
- C. Both public and private network terminals use the standard H.323 protocol to communicate
- D. None of the above statements are true

Answer: D

QUESTION 22

Under the video service, for public network calls to the private network can be changed to private network calls to the public network, the public and private network traversal technology used is generally (). (2 answers).

- A. NAT
- B. SNP
- C. ALG
- D. H.460

Answer: A

QUESTION 23

Which of the following belongs to the extension request (). (3 answers).

- A. MESSAGE
- B. PUBLISH
- C. OPTIONS
- D. NOTIFY

Answer: ABD

QUESTION 24

MP mainly completes those functions () later. (2 answers).

- A. Code circulation

- B. Call
- C. Rate adaptation
- D. Conference Control

Answer: AC

QUESTION 25

Sendto[(218.5.64.98:18616)][59285094444][0x00000065:err_reg_wrong_account_or_password]]
From the above logs, you can tell that the reason for the registration failure is ().

- A. Account password error
- B. CIDR Block Registration Restriction
- C. Cinder segment bandwidth limit
- D. Communication line exception

Answer: A

QUESTION 26

At DVI output, the 9039S and 9039A can support a primary and secondary input resolution of 1080P 60fps, in which case the secondary can reach (). The resolution of .

- A. 1080P
- B. 7201
- C. 10801
- D. 720P

Answer: A

QUESTION 27

In the MCU Web page, the format of the exported address book information is ().

- A. vcf
- B. xml
- C. dat
- D. cap

Answer: A

QUESTION 28

A meeting can support up to () group multi-screen.

- A. 1
- B. 12
- C. 24
- D. 96

Answer: C

QUESTION 29

Avenues for improving architectural acoustics include ().

- A. Low reverberation time
- B. Low background noise
- C. Low stairway noise
- D. Low controllable noise

Answer: ABC

QUESTION 30

Network recording supports downloading the recording file to the local area in () format, and supports local playback.

- A. FLV
- B. WMV
- C. RMVB
- D. MTV

Answer: A

QUESTION 31

In video conferencing, the empty field noise is required not to be greater than ().

- A. 36dB
- B. 38dB
- C. 40dB
- D. 34dB

Answer: C

QUESTION 32

H.245 The main signaling consists of ().

- A. Capacity Negotiation
- B. The Master-Slave decides
- C. Call request
- D. Open/Close Logical Channel

Answer: ABD

Thank You for Trying Our Product

Passleader Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.passleader.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER
NETWORKS



EMC²
where information lives

10% Discount Coupon Code: ASTR14