

**Exam Code:** e22-141

**Exam Name:** emc legato cert networker 7 x specialist

**Vendor:** EMC

**Version:** DEMO

## Part: A

1: A tape is brought from another NetWorker server. scanner does not update the client file index, although the Client resource was created on the new NetWorker server. Which two should you check? (Choose two.)

- A.Client ID
- B.Group attribute
- C.client name Aliases
- D.Remote Access attribute

**Correct Answers: A C**

2: Which two commands can you use to recover a single file directly from tape? (Choose two.)

- A.scanner -S ssid devicename filename | uasm -rv
- B.scanner -S ssid devicename | uasm -rv filename
- C.scanner -S ssid devicename | uasm -rv -m source=dest filename
- D.scanner -i -S ssid devicename | rsh client name '(cd destdir; uasm -rv filename)'

**Correct Answers: B C**

3: scanner -v /dev/rmt/1cbn returns the following:

please enter record size for this volume ('q' to quit)

What causes this?

- A.The volume label is corrupted or unreadable.
- B.The volume label is written by a pre-NetWorker 7.x version.
- C.scanner cannot read the volume label because the volume is not mounted.
- D.scanner cannot read the volume label because the volume is not rewound.

**Correct Answers: A**

4: A volume will be scanned into a new offsite NetWorker server to recover a client. Currently this client does not exist on the new NetWorker server. Which two resources does the scanner command require to exist on the new NetWorker server? (Choose two.)

- A.the original pool
- B.the original group
- C.the original client
- D.the original device

**Correct Answers: A C**

5: You backed up some data on a NetWorker storage node in evaluation mode. The evaluation period expired before you installed the storage node enabler code. Which statement is correct?

- A.You cannot recover the backed-up data to the storage node.
- B.You cannot recover the backed-up data to the NetWorker server.
- C.You can delete the expired storage node license and re-create it using the same code.
- D.You can recover the backed-up data to the storage node if you have a jukebox enabler.

**Correct Answers: A**

6: Storage nodes sn-1(Solaris) and sn-2(Windows) share a tape drive in a DDS environment. A tape has been labeled and written using sn-1. When trying to read the same tape using sn-2, block size errors occur. What is wrong?

- A.Sleep timers are not correctly set.
- B.The tape is labeled with the wrong block size.
- C.The tape is labeled under a different NetWorker version.
- D.The written block size cannot be handled by HBA/SCSI controller on sn-2.

**Correct Answers: D**

7: In a directed recovery, the NetWorker server named Bongo is the administering client. Flute is the source client and Clarinet is the destination client. How should the NetWorker administrator configure remote access rights to successfully run the directed recovery?

- A.in Flute's Client Resource Remote Access attribute, list root@Clarinet
- B.in Clarinet's Client Resource Remote Access attribute, list root@Bongo and root@Flute
- C.in Bongo's Client Resource Remote Access attribute, list root@Flute and root@Clarinet
- D.in Flute's Client Resource Remote Access attribute, list root@Bongo and root@Clarinet

**Correct Answers: D**

8: Which statement is true about the Remote Access All Clients privilege and the Remote Access attribute?

- A.Both must be configured to perform a directed recovery.
- B.The Remote Access attribute is required in cluster environments only.
- C.The Remote Access All Clients privilege overrides the Remote Access attribute.
- D.A user who is already defined as an administrator of the NetWorker server must be included in this attribute.

**Correct Answers: C**

9: What is the result of leaving the /nsr/res/servers file empty on a client?

- A.Any NetWorker server is able to initiate a backup of that client.
- B.All backups will fail with the error "Cannot request command execution."
- C.The client can be backed up by any NetWorker server, providing the server resides within the same subnet.
- D.Before a NetWorker server can initiate a save of that client, it is prompted for an administrative user name and password.

**Correct Answers: A**

10: What are two methods used to authorize NetWorker servers Horn and Flute to back up client Tuba with the least security risk? (Choose two.)

- A.Configure nsrexecd to use nsrexecd -s Horn -s Flute.
- B.Remove all entries from /nsr/res/servers file on Tuba and restart nsrexecd service.
- C.Make Flute and Horn the only entries in the /nsr/res/servers file on Tuba and restart nsrexecd.
- D.Stop the nsrexecd service on Tuba and run the command "nsrexecd -i ipaddress\_of\_Horn -i ipaddress\_of\_Flute."

**Correct Answers: A C**