



Vendor: Cisco

Exam Code: 642-467


Exam Name: Integrating Cisco Unified Communications Applications v8.0 (CAPPS v8.0)

Version: DEMO

QUESTION 1

Refer to the exhibit. The Allow Connections From Untrusted IP Addresses option is enabled in the SMTP Server Configuration.

What is the alternative configuration if this check box was not checked?



SMTP Server Configuration

SMTP Server Configuration Edit Refresh Help

Save

SMTP Server Configuration

SMTP Port # 25

SMTP Domain* uc801

Limit Number of Simultaneous Client Connections 20

Limit Size of Message 10000 Kilobytes

Limit Messages Accepted per SMTP Session 10

Limit Number of Recipients per Message 15000

Delivery Retry Timeout 240 Minutes

Allow Connections From Untrusted IP Addresses

Require Authentication From Untrusted IP Addresses

Transport Layer Security From Untrusted IP Addresses is: Required

- A. The Require Authentication From Untrusted IP Addresses check box must be checked.
- B. The VPIM remote users must be added as contacts.
- C. The IP address access list should be configured to explicitly allow IP addresses from remote connections.
- D. No alternatives are available.

Answer: C

QUESTION 2

When you are using Cisco Unified RTMT to troubleshoot inbound VPIM messages on Cisco Unity Connection, which of the following services is most useful for trace analysis?

- A. Connection Conversation Manager
- B. Connection Message Transfer Agent
- C. Connection SMTP Server
- D. Connection Digital Networking Replication

Answer: B

QUESTION 3

Refer to the exhibit. The trace shows an inbound VPIM message to Cisco Unity Connection, which has been networked with Cisco Unity Express.

What is the location ID for Cisco Unity Connection?

```
x-receiver: <2001@10.1.5.15>
Received: from 10.1.131.2 (10.1.131.2) by UC801 with Connection SMTP Server; Thu, 27 May 2010 22:21:26 UTC+0000
To: <2001@10.1.5.15>
From: pbrown<4001@10.1.131.2>
Date: Thu, 27 May 2010 15:05:26 -0700 (PDT)
MIME-Version: 1.0 (Voice 2.0)
Content-Type: Multipart/Voice-Message; Version=2.0;
        Boundary="==VpimMsg==1274998886689"
Content-Transfer-Encoding: 7bit
Message-ID: <FTX1244A1LJ-NME-FOC12383QD9-1274996486515>

--==VpimMsg==1274998886689
Content-Type: text/directory; charset=us-ascii; profile=vCard
Content-Transfer-Encoding: 7bit
Content-Disposition: attachment; filename="pbrown.vcf"

BEGIN:vCard
FN:pbrown
EMAIL;TYPE=INTERNET;TYPE=VPIM:4001@10.1.131.2
TEL:4001
VERSION: 3.0
END:vCard
```

- A. UC801
- B. 801
- C. Location ID is not transmitted in VPIM.
- D. 4001
- E. 127

Answer: C

QUESTION 4

Which six of the following commands are necessary to configure two ephone-dns that will provide MWI on and off functions for Cisco Unity Express? Extension 2598 turns off MWI, extension 2599 turns on MWI, and extensions use four digits? (Choose six.)

- A. extension 2598....
- B. ephone-dn 10
- C. number 2598....
- D. mwi enable
- E. number 2599....
- F. mwi on
- G. ephone-dn 11
- H. mwi off

Answer: BCEFGH

QUESTION 5

Which email integration will allow a Lotus Notes client to retrieve emails from Cisco Unity Express?

- A. MIME
- B. SMTP
- C. JTAPI

- D. CTIQBE
- E. IMAP
- F. Cisco Unity Express email infrastructure

Answer: E

QUESTION 6

If a notification profile is configured for an end user who requires a notification be sent to their work phone, cell phone, and text pager, how many notification schedules are required?

- A. A single notification schedule is required for a notification profile.
- B. Two notification schedules are required--one for each external device.
- C. Three notification schedules are required--one for each device in the notification profile.
- D. Two notification schedules are required--one for internal devices and one for external devices.

Answer: C

QUESTION 7

When changing a user password in Cisco Unity Express, how is that change propagated to Cisco Unified Communications Manager Express?

- A. The Cisco Unity Express administrator must click Synchronize Information under the Administration menu.
- B. The change is automatic; no Cisco Unified Communications Manager Express administrator intervention is required.
- C. The Cisco Unified Communications Manager Express administrator needs to manually update the user password changes.
- D. Cisco Unified Communications Manager Express uses JTAPI to periodically synchronize the user information between Cisco Unified Communications Manager Express and Cisco Unity Express.

Answer: B

QUESTION 8

Which configuration will create a trigger for Cisco Unity Express so that when Cisco Unified Communications Manager Express callers dial extension 4001, they are connected with voice mail?

- A. ccn trigger jtapi phonenumber 4001 application voicemail max sessions 6 end trigger
- B. ccn trigger sip phonenumber 4001 application "voicemail" max sessions 2 end trigger
- C. ccn trigger jtapi phonenumber 4001 application autoattendant enabled max sessions 6 end trigger
- D. ccn trigger sip phonenumber 4001 application "voicemail" enabled max sessions end trigger

Answer: D

QUESTION 9

Cisco Unified Communications Manager is being integrated with Cisco Unity Connection using SCCP. What should the Device Name Prefix be on the Cisco Unity Connection server if the Cisco Unified Communications Manager voice mail server ports are configured using the name CiscoUM1?

- A. CiscoUM1
- B. CUCM
- C. CUCM-1
- D. CiscoUM1-VI
- E. CUCM-V1
- F. CiscoUM1-V1

Answer: D

QUESTION 10

Drag and Drop Question

Drag the required SIP Trunk Security Profile settings for Cisco Unified Presence integration from the left and drop them in the spaces on the right.

Accept Unsolicited Notification	
Enable Digest Authentication	
Accept Replaces Header	
Accept Out-of-Dialog REFER	
Transmit Security Status	
Enable Application Level Authorization	
Accept Presence Subscription	

Answer:

Drag the required SIP Trunk Security Profile settings for Cisco Unified Presence integration from the left and drop them in the spaces on the right.

Accept Unsolicited Notification	Accept Unsolicited Notification
Enable Digest Authentication	Accept Replaces Header
Accept Replaces Header	Accept Out-of-Dialog REFER
Accept Out-of-Dialog REFER	Accept Presence Subscription
Transmit Security Status	
Enable Application Level Authorization	
Accept Presence Subscription	

QUESTION 11

Which of the following statements best describes blind addressing when implementing VPIM in Cisco Unity Connection?

- A. Blind addressing is used when the voice-mail user at the remote system is unavailable.
- B. Blind addressing is used by VPIM to send messages to a remote user when the user is not defined as a contact in Cisco Unity Connection.
- C. Blind addressing is a method that is used when the LRU reaches the maximum number of allowable entries.
- D. Blind addressing is only used when networking with Cisco Unity Express systems.

Answer: B

Thank You for Trying Our Product

PassLeader Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad.**
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.passleader.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER
NETWORKS



EMC²
where information lives®

10% Discount Coupon Code: STNAR2014