

Exam Code: 9A0-702

Exam Name: ColdFusion MX 7 Developer Exam

Vendor: Adobe

Version: DEMO

Part: A

1: What attribute of the <cffunction> tag is used to make a ColdFusion component method accessible as a web service?

- A.access = "public"
- B.access = "remote"
- C.webservice = "yes"
- D.returnType = "webservice"

Correct Answers: B

2: What are exception types for the <cfcatch> tag? (Choose THREE)

- A.ftp
- B.xml
- C.lock
- D.security
- E.database

Correct Answers: C D E

3: What attributes of the <cffunction> tag are optional in a ColdFusion component, but required if the method is used as a web service? (Choose TWO)

- A.Name
- B.Roles
- C.Access
- D.ReturnType

Correct Answers: C D

4: What happens to the data because the OUTPUT attribute is NOT used?

<cfwddx action="CFML2WDDX" input="#aCart#">

- A.nothing the page returns a syntax error
- B.data is serialized but no data is outputted
- C.data is serialized and outputted to the page
- D.data is serialized and placed in the special variable wOutput

Correct Answers: C

5: What is added to a URL to access the WSDL content for a ColdFusion web service?

- A./wsdl
- B.?wsdl
- C.wsdl=yes
- D.method=wsdl

Correct Answers: B

6: What expression displays the string "Corfield"?

<employees>
<employee id="1">

```

<firstname>Raymond</firstname>
<lastname>Camden</lastname>
</employee>
<employee id="2">
<firstname>Sean</firstname>
<lastname>Corfield</lastname>
</employee>
</employees>
A.employees.employee.lastname[2]
B.employees.employee[2].lastname
C.employees.xmlchildren[2].lastname.xmlText
D.employees.xmlchildren[2].xmlchildren[2].lastname

```

Correct Answers: C

7: What is added to publish a CFC method as a WebService method?

- A.access="remote" attribute to the <cffunction> tag
- B.webservice="true" attribute to the <cffunction> tag
- C.access="remote" attribute to the <cfcomponent> tag
- D.webservice="true" attribute to the <cfcomponent> tag

Correct Answers: A

8: In what way are Web services consumed in a CFML page? (Choose TWO)

- A.<cfhttp>
- B.<cfinvoke>
- C.<cfwebserver>
- D.<cfcomponent>
- E.createObject() within a <cfscript> block

Correct Answers: B E

9: What is NOT a means for invoking a web service?

- A.<cfhttp>
- B.<cfinvoke>
- C.<cfservice>
- D.createObject()

Correct Answers: C

10: In which order do the exception handling strategies listed provide increasingly more control over the application and code?

- A.cferror ; cftry ; Site-Wide Error Template
- B.Site-Wide Error Template ; cferror ; cftry
- C.cftry ; Site-Wide Error Template ; cferror
- D.Site-Wide Error Template ; cftry ; cferror

Correct Answers: B

11: What is an SQL 'Left Outer Join'?

- A.retrieves all rows from the LEFT table and only related rows from the RIGHT table
- B.retrieves all rows from the RIGHT table and only related rows from the LEFT table
- C.retrieves the related rows of the third table when the first two tables have an inner join
- D.assigned NULL values to all empty columns in the LEFT table that do not match the RIGHT table

Correct Answers: A

12: What <cfquery> attributes are used in the implementation of query-based caching? (Choose TWO)

- A.cachedtime
- B.cachedafter
- C.cachedquery
- D.cachedwithin
- E.querycached

Correct Answers: B D

13: What is NOT a valid method of caching a query recordset over time?

- A.store the query object in the Application scope
- B.use cachedWithin attribute of the <cfquery> tag
- C.use the cachedAfter attribute of the <cfquery> tag
- D.wrap the <cfcache> tag around the <cfquery> tag

Correct Answers: D

14: What method is NOT used to return data to a ColdFusion page from a database stored procedure call?

- A.<cfquery> tag to return result sets
- B.<cfspresult> tag to return result sets
- C.<cfprocresult> tag to return result sets
- D.<cfproccparam> tag to return output parameters

Correct Answers: B

15: In many development environments, URL or form variables in a dynamic query can append malicious SQL statements to existing queries. What ColdFusion tag is needed to solve this problem?

- A.<cfreturn>
- B.<cfparameter>
- C.<cfqueryparam>
- D.<cfprocessingdirective>

Correct Answers: C

16: What tags are used to independently execute a stored procedure? (Choose TWO)

- A.<cfquery>
- B.<cfinvoke>

- C.<cfexecute>
- D.<cfstoredproc>
- E.<cfprocparam>

Correct Answers: A D

17: What clauses are valid for an SQL UPDATE statement? (Choose TWO)

- A.SET
- B.INTO
- C.WHERE
- D.VALUES

Correct Answers: A C

18: How does the WHERE clause affect the SELECT statement?

SELECT *

FROM Employee

WHERE 1=1

- A.an error occurs
- B.returns the first row
- C.all rows are returned
- D.only returns the row with the primary key = 1

Correct Answers: C

19: What condition is used in a WHERE clause to determine if a database column has a NULL value?

- A.columnName = NULL
- B.columnName = 'NULL'
- C.columnName IS NULL
- D.columnName IS 'NULL'

Correct Answers: C

20: What is the problem with the cached query code?

```
<cfquery name="qGetEmp" datasource="Coffee_Valley"
```

```
cachedwithin="CreateTimeSpan(0,0,0,0)">
```

```
SELECT Emp_ID, Emp_Name, Salary
```

```
FROM Employee
```

```
</cfquery>
```

- A.cachedwithin is not a valid attribute of <cfquery>.
- B.It is missing the pound signs around CreateTimeSpan().
- C.Since there is no time value in the CreateTimeSpan() function, it will not work.
- D.It should use the CreateDate() function instead of the CreateTimeSpan() function.

Correct Answers: B